


DEAD FRONT LPSC/LPSM POWR-SAFE FUSEHOLDERS



Description

Littelfuse POWR-SAFE Dead Front holders provide optimum protection to personnel for Class CC and Midget-Style fuses.

Dimensions in inches (mm)



Features/Benefits

- Indicating and non-indicating options available
- 1-, 2-, 3- and 4-pole configurations
- Easy installation and fuse removal with no additional pullers or tools required
- 35 mm DIN Rail Mountable
- Ventilated design for cooler operation

Specifications

Voltage Rating:	600 VAC/DC
Ampere Rating:	30 A
Interrupting Rating:	200 kA (Class CC) 100 kA (Midget)
Terminal Type:	Pressure plate
Suggested Torque:	17.7 in-lbs
Wire Range:	#8–#14 CU
Material:	Thermoplastic
Approvals:	UL Listed (LPSC File No. E14721) UL Recognized (LPSM File No. E14721) CSA Certified (LPSC/LPSM File No. LR7316) CE Certified

Ordering Information

INDICATING CATALOG/SYSTEM#		NON-INDICATING CATALOG/SYSTEM#		FUSE TYPE	POLES
LPSC0001ID	LPSC0001ZXID	LPSC001	LPSC0001Z	Class CC	1
LPSC0002ID	LPSC0002ZXID	LPSC002	LPSC0002Z	Class CC	2
LPSC0003ID	LPSC0003ZXID	LPSC003	LPSC0003Z	Class CC	3
LPSC0004ID	LPSC0004ZXID	LPSC004	LPSC0004Z	Class CC	4
LPSM0001ID	LPSM0001ZXID	LPSM001	LPSM0001Z	Midget	1
LPSM0002ID	LPSM0002ZXID	LPSM002	LPSM0002Z	Midget	2
LPSM0003ID	LPSM0003ZXID	LPSM003	LPSM0003Z	Midget	3
LPSM0004ID	LPSM0004ZXID	LPSM004	LPSM0004Z	Midget	4

Multi-pole Assembly Kit: System No. CYHP001
(Kit contains 20 connector pinners and 10 handle pins.)
Pincer: CYHP002
Pin: CYHP003

Web Resources

Sample requests, downloadable CAD drawings and other technical information: www.littelfuse.com/lpsc
www.littelfuse.com/lpsm

Recommended Fuses

Class CC
Midget-Style (10 X 38 mm)